


IKE64441FB





Combine two zones to cook more

The 6000 Bridge Induction Hob can easily cope when you're cooking with bigger pans. The Bridge button links two cooking zones together to fit any large or long pan. The bridged zone will share the same temperature and time setting.

This hob can easily cope when you're cooking large amounts – or simply with bigger pans. Just touch the Bridge button to link and control two cooking zones together to fit any large or long pan. Sharing the same temperature and time setting, the linked zones are ideal when you're cooking for dinner parties or bigger

Product Benefits & Features



Combine 2 cooking zones with Bridge

The Bridge function combines two cooking zones together to fit any large or long pan. Sharing the same temperature and time setting, the linked zones are ideal when you're cooking for dinner parties or bigger celebrations.

- Automax function
- · Residual heat indicators
- Powerful booster
- 15 stage digital power level displays
- Child safety control lock
- · Control lock
- Auto safety switch off
- Front left: 1 large induction zone with booster
- Front right: 1 small induction zone with booster



Hob2Hood®: The hands-free hood

The Hob2Hood® function connects the hob and the hood. The cooker hood automatically adjusts the fan speed based on the heat, without lifting a finger. For powerful extraction when searing. And quieter extraction when simmering.

Less steps and more control with Direct Touch Controls



The Direct Touch Controls user interface uses intuitive numbers 1-14 so you can set the right temperature right away without having to toggle through the plus and minus buttons.

Quicker heat for extra speed with PowerBoost

A blast of fast. No more waiting around for pots to boil. The PowerBoost function gives you an instant burst of heat. PowerBoost is perfect for tasks that require you to boil a large pot of water quickly.

Hob timer. Built for precision

The built in hob timer can be set up to one hour, and will automatically power the hob down when it elapses. For effortlessly precise results.



IKE64441FB

Product Specification

Plug	No
Hobs Dimensions	590x520
Aperture dimensions HxWxD in mm	44x560x490
Radius cutting	5
Total electricity loading, W	7350
Hob safety	Automatic Switch Off
Left Front - Power/Diameter	2300/3200W/210mm
Rear - Power/Diameter	2300/3200W/210mm
Right front - Power/Diameter	1400/2500W/145mm
Right rear - Power/Diameter	1800/2800W/180mm
Gas supply: natural gas	No
Gas replacement	No
Gas replacement	No
Residual heat indicator	4
Led Colour	Red
ProdPartCode	E - Generic Partner All

